

# STARPOWER

SEMICONDUCTOR

**IGBT**

## GD1000HFX170P2S

**1700V/1000A 2 in one-package**

### General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as wind power.


### Features

- Low  $V_{CE(sat)}$  Trench IGBT technology
- 10 $\mu$ s short circuit capability
- $V_{CE(sat)}$  with positive temperature coefficient
- Maximum junction temperature 175°C
- Enlarged Diode for regenerative operation
- Isolated copper baseplate using DBC technology
- High power and thermal cycling capability

### Typical Applications

- High Power Converter
- Wind Power
- Auxiliary Inverter

### Equivalent Circuit Schematic



**Absolute Maximum Ratings**  $T_C=25^{\circ}\text{C}$  unless otherwise noted**IGBT**

Symbol	Description	Value	Unit
$V_{CES}$	Collector-Emitter Voltage	1700	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C=25^{\circ}\text{C}$	1604	A
	@ $T_C=100^{\circ}\text{C}$	1000	A
$I_{CM}$	Pulsed Collector Current $t_p=1\text{ms}$	2000	A
$P_D$	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	6.25	kW

**Diode**

Symbol	Description	Value	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage	1700	V
$I_F$	Diode Continuous Forward Current	1000	A
$I_{FM}$	Diode Maximum Forward Current $t_p=1\text{ms}$	2000	A

**Module**

Symbol	Description	Value	Unit
$T_{jmax}$	Maximum Junction Temperature	175	$^{\circ}\text{C}$
$T_{jop}$	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range	-40 to +150	$^{\circ}\text{C}$
$V_{ISO}$	Isolation Voltage RMS, $f=50\text{Hz}$ , $t=1\text{min}$	4000	V

**IGBT Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=1000\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		1.95	2.40	V	
		$I_C=1000\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		2.40			
		$I_C=1000\text{A}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}$		2.50			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=40.0\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.6	6.2	6.8	V	
$I_{CES}$	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			5.0	mA	
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA	
$R_{Gint}$	Internal Gate Resistance			2.3		$\Omega$	
$C_{ies}$	Input Capacitance	$V_{CE}=25\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		108		nF	
$C_{res}$	Reverse Transfer Capacitance			2.63		nF	
$Q_G$	Gate Charge	$V_{GE}=-15\dots+15\text{V}$		9.43		$\mu\text{C}$	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=900\text{V}, I_C=1000\text{A}, R_{Gon}=1.2\Omega, R_{Goff}=1.8\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		468		ns	
$t_r$	Rise Time			95		ns	
$t_{d(off)}$	Turn-Off Delay Time			850		ns	
$t_f$	Fall Time			363		ns	
$E_{on}$	Turn-On Switching Loss			292		mJ	
$E_{off}$	Turn-Off Switching Loss			230		mJ	
$t_{d(on)}$	Turn-On Delay Time		$V_{CC}=900\text{V}, I_C=1000\text{A}, R_{Gon}=1.2\Omega, R_{Goff}=1.8\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		480		ns
$t_r$	Rise Time				120		ns
$t_{d(off)}$	Turn-Off Delay Time			1031		ns	
$t_f$	Fall Time			613		ns	
$E_{on}$	Turn-On Switching Loss			439		mJ	
$E_{off}$	Turn-Off Switching Loss			325		mJ	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=900\text{V}, I_C=1000\text{A}, R_{Gon}=1.2\Omega, R_{Goff}=1.8\Omega, V_{GE}=\pm 15\text{V}, T_j=150^\circ\text{C}$			480		ns
$t_r$	Rise Time				120		ns
$t_{d(off)}$	Turn-Off Delay Time			1040		ns	
$t_f$	Fall Time			708		ns	
$E_{on}$	Turn-On Switching Loss			447		mJ	
$E_{off}$	Turn-Off Switching Loss			347		mJ	
$I_{SC}$	SC Data		$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}, V_{CC}=1300\text{V}, V_{CEM} \leq 1700\text{V}$		4000		A

**Diode Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_F$	Diode Forward Voltage	$I_F=1000\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.85	2.30	V
		$I_F=1000\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		2.00		
		$I_F=1000\text{A}, V_{GE}=0\text{V}, T_j=150^\circ\text{C}$		2.05		
$Q_r$	Recovered Charge	$V_R=900\text{V}, I_F=1000\text{A},$ $-di/dt=9200\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=25^\circ\text{C}$		270		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			1155		A
$E_{rec}$	Reverse Recovery Energy			132		mJ
$Q_r$	Recovered Charge	$V_R=900\text{V}, I_F=1000\text{A},$ $-di/dt=9200\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=125^\circ\text{C}$		451		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			1260		A
$E_{rec}$	Reverse Recovery Energy			241		mJ
$Q_r$	Recovered Charge	$V_R=900\text{V}, I_F=1000\text{A},$ $-di/dt=9200\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=150^\circ\text{C}$		528		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			1250		A
$E_{rec}$	Reverse Recovery Energy			294		mJ

**NTC Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$R_{25}$	Rated Resistance			5.0		$\text{k}\Omega$
$\Delta R/R$	Deviation of $R_{100}$	$T_C=100^\circ\text{C}, R_{100}=493.3\Omega$	-5		5	%
$P_{25}$	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K
$B_{25/80}$	B-value	$R_2=R_{25}\exp[B_{25/80}(1/T_2-1/(298.15\text{K}))]$		3411		K
$B_{25/100}$	B-value	$R_2=R_{25}\exp[B_{25/100}(1/T_2-1/(298.15\text{K}))]$		3433		K

**Module Characteristics**  $T_c=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
$L_{CE}$	Stray Inductance		10		nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal to Chip		0.20		m $\Omega$
$R_{thJC}$	Junction-to-Case (per IGBT)			24.0	K/kW
	Junction-to-Case (per Diode)			48.0	
$R_{thCH}$	Case-to-Heatsink (per IGBT)		9.0		K/kW
	Case-to-Heatsink (per Diode)		18.0		
	Case-to-Heatsink (per Module)		3.0		
M	Terminal Connection Torque, Screw M4	1.8		2.1	N.m
	Terminal Connection Torque, Screw M8	8.0		10	
	Mounting Torque, Screw M5	3.0		6.0	
G	Weight of Module		1210		g




Fig 1. IGBT Output Characteristics




Fig 2. IGBT Transfer Characteristics




Fig 3. IGBT Switching Loss vs.  $I_c$




Fig 4. IGBT Switching Loss vs.  $R_g$




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristics




Fig 8. Diode Switching Loss vs.  $I_F$




Fig 9. Diode Switching Loss vs.  $R_G$




Fig 10. Diode Transient Thermal Impedance





Fig 11. NTC Temperature Characteristic




**Circuit Schematic**



**Package Dimensions**

Dimensions in Millimeters



## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.