

STARPOWER

SEMICONDUCTOR™

IGBT

GD300HTL120C7S

Preliminary

Molding Type Module**1200V/300A 6 in one-package**

General Description

STARPOWER IGBT power module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as general inverters and UPS.



Features

- Low $V_{CE(sat)}$ SPT+ IGBT technology
- Low switching losses
- 10 μ s short circuit capability
- Square RBSOA
- $V_{CE(sat)}$ with positive temperature coefficient
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology

Typical Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

IGBT-inverter $T_C=25^\circ\text{C}$ unless otherwise noted**Maximum Rated Values**

Symbol	Description	GD300HTL120C7S	Units
V_{CES}	Collector-Emitter Voltage @ $T_j=25^\circ\text{C}$	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^\circ\text{C}$	560	A
	@ $T_C=100^\circ\text{C}$	300	
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	600	A
P_{tot}	Total Power Dissipation @ $T_j=175^\circ\text{C}$	2206	W

Off Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$T_j=25^\circ\text{C}$	1200			V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V},$ $T_j=25^\circ\text{C}$			5.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V},$ $T_j=25^\circ\text{C}$			400	nA

On Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=12\text{mA}, V_{CE}=V_{GE},$ $T_j=25^\circ\text{C}$	5.0	6.2	7.0	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=300\text{A}, V_{GE}=15\text{V},$ $T_j=25^\circ\text{C}$		1.90	2.35	V
		$I_C=300\text{A}, V_{GE}=15\text{V},$ $T_j=125^\circ\text{C}$		2.10		

Switching Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
Q_G	Gate charge	$V_{GE}=-15\dots+15\text{V}$		3.2		μC
E_{on}	Turn-On Switching Loss	$V_{CC}=600\text{V}, I_C=300\text{A},$ $R_G=3.3\Omega, V_{GE}=\pm 15\text{V},$ $T_j=25^\circ\text{C}$		32		mJ
E_{off}	Turn-Off Switching Loss			19		mJ
E_{tot}	Total Switching Loss			51		mJ
E_{on}	Turn-On Switching Loss	$V_{CC}=600\text{V}, I_C=300\text{A},$ $R_G=3.3\Omega, V_{GE}=\pm 15\text{V},$ $T_j=125^\circ\text{C}$		43		mJ
E_{off}	Turn-Off Switching Loss			32		mJ
E_{tot}	Total Switching Loss			75		mJ

$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=300A,$ $R_G=3.3\Omega, V_{GE}=\pm 15V,$ $T_j=25^\circ C$		135		ns
t_r	Rise Time			65		ns
$t_{d(off)}$	Turn-Off Delay Time			425		ns
t_f	Fall Time			55		ns
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=300A,$ $R_G=3.3\Omega, V_{GE}=\pm 15V,$ $T_j=125^\circ C$		150		ns
t_r	Rise Time			65		ns
$t_{d(off)}$	Turn-Off Delay Time			485		ns
t_f	Fall Time			75		ns
C_{ies}	Input Capacitance	$V_{CE}=25V, f=1Mhz,$ $V_{GE}=0V$		22.3		nF
C_{oes}	Output Capacitance			1.56		nF
C_{res}	Reverse Transfer Capacitance			1.02		nF
I_{SC}	SC Data	$t_{sc}\leq 10\mu s, V_{GE}\leq 15V,$ $T_j=125^\circ C, V_{CC}=600V,$ $V_{CEM}\leq 1200V$		1500		A
R_{Gint}	Internal Gate Resistance			0.7		Ω

DIODE-inverter $T_C=25^\circ C$ unless otherwise noted

Maximum Rated Values

Symbol	Description	GD300HTL120C7S	Units
V_{RRM}	Collector-Emitter Voltage @ $T_j=25^\circ C$	1200	V
I_F	DC Forward Current @ $T_C=80^\circ C$	300	A
I_{FRM}	Repetitive Peak Forward Current $t_p=1ms$	600	A

Characteristics Values

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_F=300A, V_{GE}=0V$	$T_j=25^\circ C$	1.80	2.20	V
			$T_j=125^\circ C$	1.85		
Q_r	Recovered Charge	$V_R=600V,$	$T_j=25^\circ C$	39		μC
			$T_j=125^\circ C$	75		
I_{RM}	Peak Reverse Recovery Current	$I_F=300A,$ $R_G=3.3\Omega,$	$T_j=25^\circ C$	249		A
			$T_j=125^\circ C$	330		
E_{rec}	Reverse Recovery Energy	$V_{GE}=-15V$	$T_j=25^\circ C$	14		mJ
			$T_j=125^\circ C$	30		


Electrical Characteristics of NTC $T_C=25^{\circ}\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
R_{25}	Rated Resistance			5.0		k Ω
$\Delta R/R$	Deviation of R_{100}	$T_C=100^{\circ}\text{C}, R_{100}=493.3\Omega$	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K

IGBT Module


Symbol	Parameter	Min.	Typ.	Max.	Units
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}, t=1\text{min}$		2500		V
L_{CE}	Stray Inductance		20		nH
$R_{\text{CC'+EE'}}$	Module Lead Resistance, Terminal to Chip @ $T_C=25^{\circ}\text{C}$		1.1		m Ω
$R_{\theta\text{JC}}$	Junction-to-Case (per IGBT)			0.068	K/W
	Junction-to-Case (per DIODE)			0.116	
$R_{\theta\text{CS}}$	Case-to-Sink (Conductive grease applied)		0.005		K/W
T_{jmax}	Maximum Junction Temperature			175	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40		125	$^{\circ}\text{C}$
Mounting Torque	Power Terminal Screw:M5	3.0		6.0	N.m
	Mounting Screw:M6	3.0		6.0	N.m
Weight	Weight of Module		910		g

Equivalent Circuit Schematic



Package Dimension

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.