

# STARPOWER

SEMICONDUCTOR™

# IGBT

## GD300SGT170C2S

Molding Type Module

1700V/300A 1 in one-package


### General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as inverters and UPS.



### Features

- Low  $V_{CE(sat)}$  Trench IGBT technology
- Low switching loss
- 10 $\mu$ s short circuit capability
- Low inductance case
- $V_{CE(sat)}$  with positive temperature coefficient
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology



Equivalent Circuit Schematic

### Typical Applications

- AC inverter drives
- Switching mode power supplies
- UPS

**Absolute Maximum Ratings**  $T_C=25^{\circ}\text{C}$  unless otherwise noted

Symbol	Description	GD300SGT170C2S	Units
$V_{CES}$	Collector-Emitter Voltage	1700	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_C$	Collector Current @ $T_C=25^{\circ}\text{C}$	550	A
	@ $T_C=80^{\circ}\text{C}$	300	
$I_{CM}$	Pulsed Collector Current $t_p=1\text{ms}$	600	A
$I_F$	Diode Continuous Forward Current @ $T_C=80^{\circ}\text{C}$	300	A
$I_{FM}$	Diode Maximum Forward Current $t_p=1\text{ms}$	600	A
$P_D$	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	2239	W
$T_{jmax}$	Maximum Junction Temperature	175	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
$V_{ISO}$	Isolation Voltage RMS, $f=50\text{Hz}$ , $t=1\text{min}$	4000	V
Mounting Torque	Power Terminal Screw:M4	1.1 to 2.0	N.m
	Power Terminal Screw:M6	2.5 to 5.0	
	Mounting Screw:M6	3.0 to 5.0	N.m

**Electrical Characteristics of IGBT**  $T_C=25^{\circ}\text{C}$  unless otherwise noted**Off Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$T_j=25^{\circ}\text{C}$	1700			V
$I_{CES}$	Collector Cut-Off Current	$V_{CE}=V_{CES}$ , $V_{GE}=0\text{V}$ , $T_j=25^{\circ}\text{C}$			5.0	mA
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}$ , $V_{CE}=0\text{V}$ , $T_j=25^{\circ}\text{C}$			400	nA

**On Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=12.0\text{mA}$ , $V_{CE}=V_{GE}$ , $T_j=25^{\circ}\text{C}$	5.2	5.8	6.4	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=300\text{A}$ , $V_{GE}=15\text{V}$ , $T_j=25^{\circ}\text{C}$		2.00	2.45	V
		$I_C=300\text{A}$ , $V_{GE}=15\text{V}$ , $T_j=125^{\circ}\text{C}$		2.40		

**Switching Characteristics**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=900V, I_C=300A,$ $R_G=4.7\Omega, V_{GE}=\pm 15V,$ $T_j=25^\circ C$		281		ns
$t_r$	Rise Time			82		ns
$t_{d(off)}$	Turn-Off Delay Time			801		ns
$t_f$	Fall Time			121		ns
$E_{on}$	Turn-On Switching Loss			70.0		mJ
$E_{off}$	Turn-Off Switching Loss			65.0		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=900V, I_C=300A,$ $R_G=4.7\Omega, V_{GE}=\pm 15V,$ $T_j=125^\circ C$		303		ns
$t_r$	Rise Time			103		ns
$t_{d(off)}$	Turn-Off Delay Time			1002		ns
$t_f$	Fall Time			203		ns
$E_{on}$	Turn-On Switching Loss			105		mJ
$E_{off}$	Turn-Off Switching Loss			94.0		mJ
$C_{ies}$	Input Capacitance	$V_{CE}=25V, f=1MHz,$ $V_{GE}=0V$		26.6		nF
$C_{oes}$	Output Capacitance			1.11		nF
$C_{res}$	Reverse Transfer Capacitance			0.88		nF
$I_{SC}$	SC Data	$t_p \leq 10\mu s, V_{GE}=15V,$ $T_j=125^\circ C, V_{CC}=1000V,$ $V_{CEM} \leq 1700V$		1200		A
$R_{Gint}$	Internal Gate Resistance			2.1		$\Omega$
$L_{CE}$	Stray Inductance				20	nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal To Chip			0.18		m $\Omega$

**Electrical Characteristics of DIODE**  $T_C=25^\circ C$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_F$	Diode Forward Voltage	$I_F=300A$	$T_j=25^\circ C$	1.80	2.20	V
			$T_j=125^\circ C$	1.90		
$Q_r$	Recovered Charge	$I_F=300A,$ $V_R=900V,$ $R_G=4.7\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$	77		$\mu C$
			$T_j=125^\circ C$	131		
$I_{RM}$	Peak Reverse Recovery Current	$I_F=300A,$ $V_R=900V,$ $R_G=4.7\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$	351		A
			$T_j=125^\circ C$	383		
$E_{rec}$	Reverse Recovery Energy	$I_F=300A,$ $V_R=900V,$ $R_G=4.7\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$	40.0		mJ
			$T_j=125^\circ C$	72.0		

**Thermal Characteristics**

<b>Symbol</b>	<b>Parameter</b>	<b>Typ.</b>	<b>Max.</b>	<b>Units</b>
$R_{\theta JC}$	Junction-to-Case (per IGBT)		0.067	K/W
$R_{\theta JC}$	Junction-to-Case (per DIODE)		0.124	K/W
$R_{\theta CS}$	Case-to-Sink (Conductive grease applied)	0.035		K/W
Weight	Weight of Module	300		g




Fig 1. IGBT Output Characteristic




Fig 2. IGBT Transfer Characteristic




Fig 3. IGBT Switching Loss vs.  $I_C$




Fig 4. IGBT Switching Loss vs.  $R_G$




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristic




Fig 8. Diode Switching Loss vs.  $I_F$




Fig 9. Diode Switching Loss vs.  $R_G$





Fig 10. Diode Transient Thermal Impedance

**Package Dimensions**

Dimensions in Millimeters





## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.