

STARPOWER

SEMICONDUCTOR

IGBT

GD80TLT120F1S


1200V/80A 3-level in one-package

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as solar power.

Features


- Low $V_{CE(sat)}$ Trench IGBT technology
- Low switching loss
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- Maximum junction temperature 175°C
- Fast & soft reverse recovery anti-parallel FWD
- Isolated heatsink using DBC technology



Typical Applications

- Solar power
- UPS
- 3-level-application

Equivalent Circuit Schematic



Absolute Maximum Ratings $T_C=25^{\circ}\text{C}$ unless otherwise noted**T1,T2 IGBT**

Symbol	Description	Value	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	110	A
	@ $T_C=90^{\circ}\text{C}$	80	A
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	160	A
P_D	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	450	W

D1,D2 Diode

Symbol	Description	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	50	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	100	A

T3,T4 IGBT

Symbol	Description	Value	Unit
V_{CES}	Collector-Emitter Voltage	600	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	93	A
	@ $T_C=65^{\circ}\text{C}$	75	A
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	150	A
P_D	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	231	W

D3,D4 Diode

Symbol	Description	Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	600	V
I_F	Diode Continuous Forward Current	60	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	120	A

Module

Symbol	Description	Value	Unit
T_{jmax}	Maximum Junction Temperature	175	$^{\circ}\text{C}$
T_{jop}	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}, t=1\text{min}$	4000	V

T1,T2 IGBT Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=80\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		2.00	2.45	V	
		$I_C=80\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		2.30			
		$I_C=80\text{A}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}$		2.35			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=3.0\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.3	5.8	6.3	V	
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			1.0	mA	
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA	
R_{Gint}	Internal Gate Resistance			/		Ω	
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		4.66		nF	
C_{res}	Reverse Transfer Capacitance			0.26		nF	
Q_G	Gate Charge	$V_{GE}=-15\dots+15\text{V}$		0.37		μC	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=350\text{V}, I_C=56\text{A}, R_G=4.0\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		76		ns	
t_r	Rise Time			12		ns	
$t_{d(off)}$	Turn-Off Delay Time			172		ns	
t_f	Fall Time			50		ns	
E_{on}	Turn-On Switching Loss			0.46		mJ	
E_{off}	Turn-Off Switching Loss			1.34		mJ	
$t_{d(on)}$	Turn-On Delay Time		$V_{CC}=350\text{V}, I_C=56\text{A}, R_G=4.0\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		77		ns
t_r	Rise Time				15		ns
$t_{d(off)}$	Turn-Off Delay Time			215		ns	
t_f	Fall Time			62		ns	
E_{on}	Turn-On Switching Loss			0.80		mJ	
E_{off}	Turn-Off Switching Loss			1.86		mJ	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=350\text{V}, I_C=56\text{A}, R_G=4.0\Omega, V_{GE}=\pm 15\text{V}, T_j=150^\circ\text{C}$			78		ns
t_r	Rise Time				16		ns
$t_{d(off)}$	Turn-Off Delay Time			225		ns	
t_f	Fall Time			66		ns	
E_{on}	Turn-On Switching Loss			0.96		mJ	
E_{off}	Turn-Off Switching Loss			2.24		mJ	
I_{SC}	SC Data		$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}, V_{CC}=360\text{V}, V_{CEM} \leq 1200\text{V}$		320		A

D1,D2 Diode Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	$I_F=50\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.75	2.20	V
		$I_F=50\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		1.65		
		$I_F=50\text{A}, V_{GE}=0\text{V}, T_j=150^\circ\text{C}$		1.65		
Q_r	Recovered Charge	$V_R=350\text{V}, I_F=56\text{A},$ $-di/dt=5000\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=25^\circ\text{C}$		5.2		μC
I_{RM}	Peak Reverse Recovery Current			105		A
E_{rec}	Reverse Recovery Energy			1.50		mJ
Q_r	Recovered Charge	$V_R=350\text{V}, I_F=56\text{A},$ $-di/dt=5000\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=125^\circ\text{C}$		7.0		μC
I_{RM}	Peak Reverse Recovery Current			114		A
E_{rec}	Reverse Recovery Energy			2.10		mJ
Q_r	Recovered Charge	$V_R=350\text{V}, I_F=56\text{A},$ $-di/dt=5000\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=150^\circ\text{C}$		8.1		μC
I_{RM}	Peak Reverse Recovery Current			118		A
E_{rec}	Reverse Recovery Energy			2.40		mJ

T3,T4 IGBT Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		1.45	1.90	V	
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		1.60			
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}$		1.70			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=1.2\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.1	5.8	6.4	V	
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			1.0	mA	
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA	
R_{Gint}	Internal Gate Resistance			/		Ω	
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		4.62		nF	
C_{res}	Reverse Transfer Capacitance				0.14		nF
Q_G	Gate Charge	$V_{GE}=-15\dots+15\text{V}$		0.80		μC	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=350\text{V}, I_C=56\text{A}, R_G=4.0\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		84		ns	
t_r	Rise Time			10		ns	
$t_{d(off)}$	Turn-Off Delay Time			180		ns	
t_f	Fall Time			87		ns	
E_{on}	Turn-On Switching Loss			0.53		mJ	
E_{off}	Turn-Off Switching Loss			1.86		mJ	
$t_{d(on)}$	Turn-On Delay Time		$V_{CC}=350\text{V}, I_C=56\text{A}, R_G=4.0\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		85		ns
t_r	Rise Time				11		ns
$t_{d(off)}$	Turn-Off Delay Time			200		ns	
t_f	Fall Time			100		ns	
E_{on}	Turn-On Switching Loss			0.66		mJ	
E_{off}	Turn-Off Switching Loss			2.20		mJ	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=350\text{V}, I_C=56\text{A}, R_G=4.0\Omega, V_{GE}=\pm 15\text{V}, T_j=150^\circ\text{C}$			86		ns
t_r	Rise Time				12		ns
$t_{d(off)}$	Turn-Off Delay Time			208		ns	
t_f	Fall Time			105		ns	
E_{on}	Turn-On Switching Loss			0.75		mJ	
E_{off}	Turn-Off Switching Loss			2.50		mJ	
I_{SC}	SC Data		$t_p \leq 6\mu\text{s}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}, V_{CC}=350\text{V}, V_{CEM} \leq 600\text{V}$		380		A

D3,D4 Diode Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V_F	Diode Forward Voltage	$I_F=60\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.50	1.95	V
		$I_F=60\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		1.40		
		$I_F=60\text{A}, V_{GE}=0\text{V}, T_j=150^\circ\text{C}$		1.40		
Q_r	Recovered Charge	$V_R=350\text{V}, I_F=56\text{A},$ $-di/dt=4000\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=25^\circ\text{C}$		1.4		μC
I_{RM}	Peak Reverse Recovery Current			38		A
E_{rec}	Reverse Recovery Energy			0.20		mJ
Q_r	Recovered Charge	$V_R=350\text{V}, I_F=56\text{A},$ $-di/dt=4000\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=125^\circ\text{C}$		2.7		μC
I_{RM}	Peak Reverse Recovery Current			45		A
E_{rec}	Reverse Recovery Energy			0.50		mJ
Q_r	Recovered Charge	$V_R=350\text{V}, I_F=56\text{A},$ $-di/dt=4000\text{A}/\mu\text{s}, V_{GE}=-15\text{V}$ $T_j=150^\circ\text{C}$		3.1		μC
I_{RM}	Peak Reverse Recovery Current			50		A
E_{rec}	Reverse Recovery Energy			0.60		mJ

NTC Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
R_{25}	Rated Resistance			22.0		$\text{k}\Omega$
$\Delta R/R$	Deviation of R_{100}	$T_C=100^\circ\text{C}, R_{100}=1486.1\Omega$	-5		5	%
P_{25}	Power Dissipation				200	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		4000		K

Module Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
R_{thJC}	Junction-to-Case (per T1,T2 IGBT)		0.303	0.333	K/W
	Junction-to-Case (per D1,D2 Diode)		0.764	0.840	
	Junction-to-Case (per T3,T4 IGBT)		0.590	0.649	
	Junction-to-Case (per D3,D4 Diode)		0.860	0.946	
R_{thCH}	Case-to-Heatsink (per T1,T2 IGBT)		0.158		K/W
	Case-to-Heatsink (per D1,D2 Diode)		0.399		
	Case-to-Heatsink (per T3,T4 IGBT)		0.309		
	Case-to-Heatsink (per D3,D4 Diode)		0.450		
	Case-to-Heatsink (per Module)		0.035		
M	Mounting Torque, Screw M4	2.0		2.2	N.m
G	Weight of Module		26		g




Fig 1. T1,T2 IGBT Output Characteristics




Fig 2. T1,T2 IGBT Transfer Characteristics




Fig 3. T1,T2 IGBT Switching Loss vs. I_C




Fig 4. T1,T2 IGBT Switching Loss vs. R_G




Fig 5. T1,T2 RBSOA




Fig 6. T1,T2 IGBT Transient Thermal Impedance




Fig 7. D1,D2 Diode Forward Characteristics




Fig 8. D1,D2 Diode Switching Loss vs. I_F




Fig 9. D1,D2 Diode Switching Loss vs. R_G




Fig 10. D1,D2 Diode Transient Thermal Impedance




Fig 11. T3,T4 IGBT Output Characteristics




Fig 12. T3,T4 IGBT Transfer Characteristics




Fig 13. T3,T4 IGBT Switching Loss vs. I_C




Fig 14. T3,T4 IGBT Switching Loss vs. R_G




Fig 15. T3,T4 RBSOA




Fig 16. T3,T4 IGBT Transient Thermal Impedance




Fig 17. D3,D4 Diode Forward Characteristics




Fig 18. D3,D4 Diode Switching Loss vs. I_F




Fig 19. D3,D4 Diode Switching Loss vs. R_G




Fig 20. D3,D4 Diode Transient Thermal Impedance









Fig 21. NTC Temperature Characteristic

Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.